

## 290.250 DGANC

Automatic Fully Enclosed  
Two Way Mitre Bandsaw



## Features

- Robust, one piece, cast iron saw bow
- NC Controls
- 99 lines for programming, fault diagnostics, machine status report
- Automatic rotation of mitre
- Positive hydraulic downfeed with automatic pressure sensing control
- 1500mm single pass vice feed length, multiple feed for longer lengths
- Fast approach 'T Bar'
- TC pads and roller bearings for square cuts
- Moveable guide arm adjustable according to section size
- Heavy duty, 3 phase motor
- Steplessly variable blade speed 20-120 m/min
- Heavy duty blade tensioning unit
- Swarf brush removes swarf from blade prior to entry into material
- Recirculating coolant pump



Automatic Mitre



Pressure sensing control valve

## CAPACITIES (mm) & SPECIFICATION

0°	230	300 x 200	230
45° R	195	130 x 100	195
45° L	200	190 x 130	200
60° R	135	130 x 95	95
Blade Size - 2910 x 27 x 0.9		Speed - 20 - 120 m/min	
Dimensions - 2900 x 1900 x 1700		Bed Height - 755	



1500mm single pass infeed

## Optional Extras



Mist Spray Lubrication



Roller Conveyors



Laser Line