

290.258 DGANC

Automatic Fully Enclosed
Two Way Mitre Bandsaw



Features

- Robust, one piece, cast iron saw bow
- NC Controls
- 99 lines for programming, fault diagnostics, machine status report
- Automatic rotation of mitre
- Positive hydraulic downfeed with automatic pressure sensing control
- Vice pressure reduction system
- 1500mm single pass vice feed length, multiple feed for longer lengths
- Fast approach 'T Bar'
- TC pads and roller bearings for square cuts
- Moveable guide arm adjustable according to section size
- Heavy duty, 3 phase motor
- Steplessly variable blade speed 20-120 m/min
- Heavy duty blade tensioning unit
- Swarf brush removes swarf from blade prior to entry into material
- Recirculating coolant pump

Continued



Automatic Mitre



Pressure sensing control valve

CAPACITIES (mm) & SPECIFICATION

			
0°	258	325 x 180	250
45° R	210	215 x 100	195
45° L	180	235 x 80	165
60° R	125	135 x 100	125
Blade Size - 2910 x 27 x 0.9		Speed – 20 - 120 m/min	
Dimensions – 2900 x 1850 x 1650		Bed Height - 755	



1500mm single pass infeed

Optional Extras



Mist Spray Lubrication



Roller Conveyors



Laser Line