Dry abrasive cutting machine TYRO for straight cut

Ref : TMS 250

STANDARD EQUIPMENT

- Grinder Ø 250 mm. Bore 22.2 mm
- Motor 4 HP, three phase 400 V
- Manual down feed
- Manual oscillation motor (**automatic optional**)
- 2 pneumatic vices
- Base in powder-coated welded sheet metal
- Wrap-around bonnet with electrical safety
- Working height : 840 mm
- Integrated 24 V lighting
- Complies with current regulations
- Equipment supplied with CE marking and CE certificate



CUTTING CAPACITIES			
Unit : mm	50	60	80x60

EQUIPMENT ON REQUEST

- **ELECTRONIC SPEED VARIATOR –** *Circumferential speed 30 to 80 m/s in 4 HP*
- **AUTOMATIC OSCILLATION of the grinding wheel –** *Faster cutting speed (nearly 2 times faster) and avoids clogging & bluing of materials (even hard ones). The electrical consumption is lower compared to a conventional machine.*
- **CUT-OFF WHEELS :** *Bore 22.2 mm - Ø 250 mm*
- **SPECIAL JAWS FOR SMALL Ø**
- **DUST COLLECTOR**

ROTY & Fils – 64 rue de la Ville-Es-Cours – Z.I. Sud – 35400 SAINT-MALO – FRANCE
Tel : +33 (0)2 99 58 40 47 E-mail : contact@roty-tyro.com www.roty-tyro.com
Version 2024