Dry abrasive cutting machine TYRO for straight cut

Ref : TMS 410

STANDARD EQUIPMENT

- Grinder Ø 406 mm. Bore 25.4 mm
- Motor 10 HP, three phase 400 V
- Manual down feed
- Manual oscillation motor (**automatic optional**)
- 2 pneumatic vices
- Base in powder-coated welded sheet metal
- Wrap-around bonnet with electrical safety
- Working height : 840 mm
- Integrated 24 V lighting
- Complies with current regulations
- Equipment supplied with CE marking and CE certificate



CUTTING CAPACITIES			
Unit : mm	100	130	220x90

EQUIPMENT ON REQUEST

- **ELECTRONIC SPEED VARIATOR –** *Circumferential speed 30 to 80 m/s*
- **AUTOMATIC OSCILLATION of the grinding wheel –** *Faster cutting speed (nearly 2 times faster) and avoids clogging & bluing of materials (even hard ones). The electrical consumption is lower compared to a conventional machine.*
- **CUT-OFF WHEELS :** *Bore 25.4 mm - Ø 350 mm*
- **DUST COLLECTOR DA 150 MP - 600 m3/h. 0.75 kw** *– drawer version with adaptation (2,50 m metal hose)*

ROTY & Fils – 64 rue de la Ville-Es-Cours – Z.I. Sud – 35400 SAINT-MALO – FRANCE
Tel : +33 (0)2 99 58 40 47 E-mail : contact@roty-tyro.com www.roty-tyro.com
Version 2024