

PROSAW

Supplying the World's Finest Machines to UK industry since 1963



karmetal

KDG 560x1050DM

Twin Column, Semi-Automatic Two-way Mitre Bandsaw



Features

- Very heavy-duty, twin column design
- Easy bow rotation for mitre cuts
- Double mitres, 45° left, 60° right with hydraulic lock
- Powerful 5.5kW blade drive motor
- Bow descends on hardened linear bearing rails
- Adjustable hydraulic regulation of the bow descent rate
- Inclined blade for optimum cutting
- Full stroke hydraulic vice with pressure regulation
- Hydraulic top clamp
- Large, fixed, datum line vice
- Simple robust controls
- Steplessly variable blade speed 25 to 90m/min
- Laser line
- Powered swarf conveyor
- Powered swarf brush
- 54mm wide blade
- Working height: 875mm
- LED strip light

PROSAW LIMITED

15 Telford Way, Kettering,
Northants, NN16 8UN

Tel: +44 (0)1536 410999

sales@proshaw.co.uk

www.proshaw.co.uk

Continued



Hydraulic Top Clamp



Vice Pressure Reduction



Swarf Conveyor

CAPACITIES (mm) & SPECIFICATION

0°	560	560 x 1050	560
45°	500	560 x 680	500
60°	450	500 x 460	450
-45°	500	560 x 800	500
Blade Size - 7145 x 54 x 1.6		Speed - 25 to 90 m/min	
Dimensions - 2200 x 3500 x 2250		Bed Height - 875	



2 off – 3m Roller Tables

Optional Extras



Long Stroke Feeder



Roller Conveyors



Measuring