

V25 Semi-automatic, Mitring, Vertical Bandsaw



CAPACITIES (mm) & SPECIFICATION

Mitre Range	60 - 0 - 60°
0°	635 Ø / 762 x 635
45°	533 Ø / 533 x 635
60° Right	368 Ø / 368 x 635
60° Left	342 Ø / 342 x 635
Table Height	1117
Blade Size	6414 x 41 x 1.3
Blade Speed	22 – 106 m/min
Motor	7.5 kW
Dimensions	4064 x 2438 x 3124
Weight	4545 kg

FEATURES

- Very heavy build
- 6° canted head
- Hydraulic powered mitring to $\pm 60^\circ$ with digital display
- Twin full-stroke hydraulic vices
- Vice pressure reduction system
- 7.5kW direct connection blade motor (no belts)
- Blade width 41mm
- 2.2kW hydraulic pump
- Hydraulic positive downfeed
- Hydraulic powered upper guide arm
- Automatic shut down if blade breaks
- Carbide pads and roller bearings on blade guide assemblies
- Hydraulic band tensioning with digital readout

- Integral flood coolant system
- Laser light & work light

OPTIONS

- Hydraulic overhead bundle clamps
- Mist spray lubrication
- Hydraulic chip conveyor
- Chip bucket with pump
- Pop-up feed rollers
- Hydraulic datum line vertical rollers
- Tall square vice inserts